



Abus door lock change

dismantle old door lock and assemble new profile cylinder lock.

Written By: Daniel Bania



INTRODUCTION

dismantle old door lock and assemble new profile cylinder lock.

[Video: <https://www.youtube.com/watch?v=bFGXYFFzaRg>]

Step 1 — determine size of the lock cylinder



- Open the door and look at the lock on the door rebate on. Here is located under the catch (latch) on the fold the screw.
- Next, turn the screw out completely and remove the lock cylinder, by turning the key to about 20 degrees to the right or left. Stuck it, you can usually resolve it by gently shaking. Sits firmly he really, he clamped often on the fitting. Loosen in this case the screws slightly and try

Step 2 — Remove door handle and square



- Now you need to remove the door handle to refer to the attached or inserted individually square can. This passes through the entire thickness of the door, the lock and the fittings throughout and moved via the lever the lock. Often must be unscrewed to its removal, the fittings. So Solve optionally their
- Screws and pull off the fittings. Depending on the manufacturer, the covers of the fittings are plugged or sometimes attached again with small screws. The must of course be removed before. The same applies to the possible fixing of the square by small Allen screw on the handle base.

Step 3 — refer mortise



- If the square removed, loosen the two screws at the top and bottom of the castle - they are back on the Türfalzseite. Now you can pull out the lock and take as a pattern to buy a new.

Step 4 — Insert New Castle



- The installation of the new castle is just like the expansion - only in reverse order. Plug the new lock so first back into the milling on the edge and fix it with the upper and lower screw.

Step 5 — mounted security fittings



- Now mount optionally the remote fittings and plug the square or, depending on the manufacturer to handle including square again. Fix it if necessary, next on the small Allen screw down on the trigger and test short, whether the square crank when.

Step 6 — Tighten screw



- Now put the cylinder, according to the detected before removing values in the proper direction, to test all functions and draw conclusion the set screw. Replace the door fittings, these often have other holes können.Achten but easily performed via template already need when selecting
- that the existing holes are also covered and that there is still plenty of door parts for attaching the new hardware is available bleibt.Schon managed. With few clicks, you have a well-functioning lock again and not be unintentionally front of a locked door. Ask? [http // www.schnelle-tueroeffnung.de](http://www.schnelle-tueroeffnung.de)

Arbeite die Schritte in umgekehrter Reihenfolge ab, um dein Gerät wieder zusammenzubauen.